IN THE CLAIMS:

Please amend the claims as follows:

1. (Currently Amended) A communications network comprising: at least one a communication virtualizer,

wherein said communication virtualizer combines multiple Ethernet packets received from a client computer into a jumbo packet,

wherein a data size of said multiple Ethernet packets received exceeds that of a maximum size supported by a Network File System (NFS) protocol, and

wherein a data size of said jumbo packet exceeds that of said maximum size supported by said NFS protocol;

a plurality of network-attached store computers connected to said communication virtualizer, wherein said plurality of network-attached store computers are configured to appear as a single available network-attached store computer; and

at least one said client computer being connected to said communication virtualizer,

wherein said client computer is adapted to send sends requests for storage to said communication virtualizer.

wherein said requests for storage are transmitted as a series of <u>standard Ethernet</u> packets, each packet comprising a portion of the request for storage, <u>and said data size for said series of standard Ethernet packets exceeds that of said maximum size supported by said NRS protocol</u>,

wherein each packet comprises a packet sequence number,

wherein said packets comprising a similar request for storage are linked together using a request identifier, said and a packet sequence number, and a client identifier and,

wherein each request for storage comprises a unique request identifier that is shared among said packets comprising said similar request, and

wherein each response packet from said store computers includes said client identifier.

- 2. (Currently Amended) The communications network according to claim 1, all the limitations of which are incorporated herein by reference, further comprising an internal network of connection nodes connecting said communication virtualizer with said network-attached store computers.
- 3. (Currently Amended) The communications network according to claim 1, all the limitations of which are incorporated herein by reference, further comprising a plurality of external network connections for facilitating a transfer of requests sent by said client computer to said communication virtualizer.
- 4. (Currently Amended) The communications network according to claim 1, all the limitations of which are incorporated herein by reference, further comprising a plurality of external connection paths for facilitating direct communication between said network-attached store computers and said client computer.
- 5. (Currently Amended) The communications network according to claim 1, all the limitations of which are incorporated herein by reference, further comprising [[an]] Ethernet networking hardware and medium access protocols for facilitating communication within said communication network.
- 6. (Currently Amended) The communications network according to claim 1, all the limitations of which are incorporated herein by reference, further comprising a Transmission Control Protocol / Internet Protocol suite for facilitating communication between said network-attached store computers and said client computer.
- 7. (Currently Amended) The communications network according to claim 1, all the limitations of which are incorporated herein by reference, further comprising a storage access

protocol for facilitating communication between a storage component within said communications network and remaining components within said communications network.

8-9. (Cancelled).

- 10. (Currently Amended) The communications network according to claim 1, all the limitations of which are incorporated herein by reference, wherein said communication virtualizer comprises a network router.
- 11. (Currently Amended) The communications network according to claim 1, all the limitations of which are incorporated herein by reference, further comprising a communication virtualizer file switch connected to a client computer and a server computer for sending requests from said client computer to said network-attached store and from said network-attached store back to said client computer.
- 12. (Currently Amended) A method of communication over a communications network, said method comprising:

sending requests for storage originated by at least one a client computer over said communications network,

wherein said requests comprise multiple standard Ethernet packets, and
wherein each of said requests has a data size exceeding that of a maximum size
supported by a Network File System (NFS) protocol;

receiving said requests for storage in at least one a communication virtualizer,

wherein said communication vitualizer combines multiple standard Ethernet

packets received from said client computer into a jumbo packet,

wherein a data size of said multiple standard Ethernet packets received exceeds
that of a maximum size supported by a Network File System (NFS) protocol, and
wherein a data size of said jumbo packet exceeds that of said maximum size
supported by said NFS protocol;

transmitting the received requests for storage to a plurality of network-attached store computers connected to said communication virtualizer, wherein said plurality of network-attached store computers are configured to appear as a single network-attached store computer, wherein said requests for storage are transmitted as a series of packets, each packet comprising a portion of the request for storage, wherein each packet comprises a packet sequence number, wherein said packets comprising a similar request for storage are linked together using a request identifier, said and a packet sequence number, and a client identifier, and wherein each request for storage comprises a unique request identifier that is shared among said packets comprising said similar request; and

transmitting, by said store computers, response packets to said communication virtualizer, wherein each of said response packets include said client identifier identifies said client computer.

13. (Currently Amended) The method according to claim 12, all the limitations of which are incorporated herein by reference, wherein said communication virtualizer, upon receiving requests from said client computer, transmits said request for storage to a chosen network-attached store computer based on a capability of said chosen network-attached store computer to properly process said request for storage.

14-15. (Cancelled).

16. (Currently Amended) The method according to claim 12, all the limitations of which are incorporated herein by reference, wherein said network-attached store computer is configured for:

receiving said requests for storage from said communication virtualizer; processing said request for storage; creating a corresponding response to said request for storage; packetizing said corresponding response; and sending said corresponding response to said communication virtualizer.

17. (Currently Amended) The method according to claim 16, all the limitations of which are incorporated herein by reference, wherein said communication virtualizer is configured for: receiving said corresponding response from said network-attached store computer; determining a chosen client computer to which said corresponding response should be routed to; and

routing said corresponding response to a chosen client computer.

- 18. (Currently Amended) The method according to claim 17, all the limitations of which are incorporated herein by reference, wherein said chosen client computer is configured for: receiving said corresponding response from said communication virtualizer; de-packetizing said corresponding response; and routing said corresponding response to an initiating application.
- 19. (Currently Amended) The method according to claim 12, all the limitations of which are incorporated herein by reference, wherein said packets are categorized from a zeroth (θ th) packet to an ith packet.
- 20. (Currently Amended) The method according to claim 19, all the limitations of which are incorporated herein by reference, wherein said communication virtualizer determines which network-attached store computer to transmit said request for storage to by examining said zeroth packet in said request.
- 21. (Cancelled).
- 22. (Currently Amended) The method according to claim 21, all the limitations of which are incorporated herein by reference, further comprising:

said network-attached store computer sending a standard Ethernet packet to said communication virtualizer in reply to a client computer request; and

said communication virtualizer dividing said standard Ethernet packet into a plurality of standard Ethernet packets to send to said client computer as a response comprising multiple standard Ethernet packets.

- 23. (Cancelled).
- 24. (Currently Amended) The communications network according to claim 1, all the limitations of which are incorporated herein by reference, wherein said communication virtualizer is adapted to translate a first protocol of said requests for storage to a second protocol different from said first protocol.
- 25. (Cancelled).
- 26. (Currently Amended) The method according to claim 12, all the limitations of which are incorporated herein by reference, wherein said communication virtualizer is adapted to translate a first protocol of said requests for storage to a second protocol different from said first protocol.
- 27. (Cancelled).